



EARTH LEAD



REGULATOR



TIG TORCH

ADJUSTABLE PULSE
HIGH FREQUENCY DC
IGNITION
FULLY ADJUSTABLE DIGITAL
STEP THROUGH CONTROL
2T-4T TRIGGER FUNCTION
40 % AT 200 AMPS
RUGGED METAL CASE
1 YEAR WARRANTY



Automatic Welding Helmet

COMPLETE WITH
WP26-4 SWITCHED TORCH
4 MTR 25MM EARTH RETURN
UNI-FLAME ARGON REG

TECHNICAL SPECIFICATIONS

Model	ATIG160P	ATIG200P
Rated input voltage /frequency (V /Hz)	Single phase AC 230V±10% 50 /60Hz	
Rated input power (Kw)	3.3	4.5
Rated input current (A)	15.3	21
Open-load voltage (V)	MMA	9
	TIG	58
Range of welding current (A)	MMA	10-160
	TIG	10-160
MMA arc-force current (A)	50	
MMA arc-starting current (A)	50	
Pulse frequency (Hz)	0.2-20	
Rated duty cycle (% @25°C)	40	
Arc-starting type	HF	
Efficiency (%)	≥80	
Cosφ	0.98	
Protection class	IP21	
Insulation class	F	
Weight (kg /lb)	9.5 /21	
Dimension LxWxH (mm /inch)	389×155×299 /16.1×6.1×11.7	



SOLE NEW ZEALAND DISTRIBUTORS OF

